

ARTEMIS 200ASF-SL



2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
24 SMD LED
45m IR Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case

10.400.000

PHOBOS 200WSF-SCA



2.0 Megapixel HDTVI Camera
1/2.9" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Power LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
Support Audio in TVI & CVI Mode
(Compatible With Dahua Recorder)

10.200.000

DEVRA 200DSF-SCA



2.0 Megapixel HDTVI Camera
1/2.9" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
2 Dual LED
30m Warmlight, 40m IR Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
Support Audio in TVI & CVI Mode
(Compatible With Dahua Recorder)

10.900.000

TITAN 200DSF-SCA



2.0 Megapixel HDTVI Camera
1/2.9" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 Dual EXIR LED
30m Warmlight, 40m IR Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
Support Audio in TVI & CVI Mode
(Compatible With Dahua Recorder)
IP67, Metal Ball, Easy Installation

14.200.000

TITAN 200WSF-SCA



2.0 Megapixel HDTVI Camera
1/2.9" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
Support Audio in TVI & CVI Mode
(Compatible With Dahua Recorder)
IP67, Metal Ball, Easy Installation

13.450.000

TITAN 500DSF-SA



5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 Dual EXIR LED
30m Warmlight, 40m IR Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP67, Metal Ball, Easy Installation

17.250.000

TITAN 500WSF-SA



5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP67, Metal Ball, Easy Installation

16.600.000

TETIS 200WSF-SCA



2.0 Megapixel HDTVI Camera
1/2.9" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
Support Audio in TVI & CVI Mode
(Compatible With Dahua Recorder)
IP67, Metal Ball, Easy Installation

13.450.000

TETIS 500WSF-SA



5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP67, Metal Ball, Easy Installation

16.600.000

POLARIS 200WLF-S



2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
4 EXIR LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case, Easy Installation

13.200.000

POLARIS 500DLF-SA



5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Dual EXIR LED
40m Warmlight, 60m IR Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

17.600.000

POLARIS 500WLF-SA



5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 EXIR LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

17.000.000

NESTOR 200DLF-S



2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Dual EXIR LED
40m Warmlight, 60m IR Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case

13.850.000

NESTOR 200WLF-S



2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
4 EXIR LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case

13.200.000

NESTOR 500DLF-SA



5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Dual EXIR LED
40m Warmlight, 60m IR Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case

17.600.000

NESTOR 500WLF-SA



5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 EXIR LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case

17.000.000

AWASIS 200DLF-S



2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 Dual EXIR LED
30m Warmlight, 40m IR Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case

13.200.000

AWASIS 200WLF-S



2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case

12.650.000

AWASIS 500DLF-SA



5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 Dual EXIR LED
30m Warmlight, 40m IR Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case

17.000.000

AWASIS 500WLF-SA



5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case

16.350.000

HELIX 200DLF-S



2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 Dual EXIR LED
30m Warmlight, 40m IR Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case

12.950.000

HELIX 200WLF-SA



2.0 Megapixel HDTVI Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case

12.950.000

HELIX 200WLF-S



2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case

12.450.000

HELIX 200WLF-S/28



2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case

12.450.000

HELIX 500DLF-SA



5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 Dual EXIR LED
30m Warmlight, 40m IR Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case

16.850.000

HELIX 500WLF-SA



5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case

16.200.000

AVILON 500WLF-SA



5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Power EXIR LED
50m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

18.300.000

KAVARIA 200WLF-S



2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
4 High Power LED
50m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case

15.200.000

KAVARIA 500WLF-S



5.0 Megapixel Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 High Power LED
50m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case

17.750.000

AC-BH7450-DS



2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
2 Power LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case

12.100.000

FARA AI ALARM BOX



15.200.000

3 Output Relay Box
1 Output With 12VDC
1 RJ45 Web Management Interface
Compatible With Z Series XVR
12VDC Input (Without Adaptor)

این محصول به وسیله کابل شبکه به رکوردرهای سری زد متصل شده و با تعریف و پیاده سازی سناریوهای مختلف از طریق رکوردر و منوی خود محصول می توان از قابلیت های تشخیص انسان و خودروی دوربین و رکوردر در جهت فعال سازی خروجی محصول استفاده نمود تا خروجی تجهیزاتی از قبیل آژیر، تلفن کننده، فرمان به دزدگیر و سایر تجهیزات فرمان پذیر را فعال کرد و از دوربین ها به عنوان دتکتور محیطی با هوش مصنوعی و دقت بسیار بالا استفاده نمود

OHD-6104ZFN-A1



29.900.000

4CH H.265 **5MP-Lite** XVR
4CH Camera + 1CH IP Camera
Preview Capacity: 4*(5MP-Lite@20)fps
Code Capacity: 4*(5MP-Lite@12/4MP-Lite@17/1080P@15/1080P-Lite@25)fps
4CH Playback
Support SMD (Human/Vehicle Clasification For 4CH)
Support Face Detection 1CH (With Special Firmware Upgarde / Not At The Same Time As SMD)
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analoge,AHD,CVI,TVI,IP)
HDMI 1080P & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

OHD-8104ZFN-4KL/A4



42.450.000

4CH H.265 **Real 5MP** XVR
4CH Camera (Analog & IP)
Preview Capacity: 4*(5MP@12)fps
Code Capacity: 4*(5MP@12/4MP@15/1080P@25)fps
4CH Playback
Support SMD (Human/Vehicle Clasification For 4CH)
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analoge,AHD,CVI,TVI,IP)
HDMI 4K & VGA Video Simultaneous Output - Analog Video Output (BNC)
1 SATA HDD Up to 10TB
4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

OHD-8104ZHN-4KL/A4



HISILICON

NEW AI Chipset



43.850.000

4CH H.265 **4K-Lite & Real 5MP** XVR
4CH Camera + 2CH IP Camera
Preview Capacity: 4*(8MP-Lite@15/5MP@12)fps
Code Capacity: 4*(8MP-Lite@15/5MP@12/4MP@16/1080P@25)fps
4CH Playback (2CH@15fps + 2CH@1fps)
Support SMD (Human/Vehicle Clasification For 4CH)
Support Face Detection
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analoge,AHD,CVI,TVI,IP)
HDMI 4K & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

OHD-6108ZFN-A1



توقف تولید

39.000.000

8CH H.265 **5MP-Lite** XVR
8CH Camera + 2CH IP Camera
Preview Capacity: 8*(5MP-Lite@12)fps
Code Capacity: 8*(5MP-Lite@6/4MP-Lite@8/1080P-Lite@16)fps
8CH Playback
Support SMD (Human/Vehicle Clasification For 8CH)
Support 1CH Face Detection (With Special Firmware Upgarde / Not At The Same Time As SMD)
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analoge,AHD,CVI,TVI,IP)
HDMI & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran & International Servers

OHD-6108ZFU-A1



New Ultra Model



39.000.000

8CH H.265 **5MP-Lite** XVR
8CH Camera + 2CH IP Camera
Preview Capacity: 8*(5MP-Lite@12)fps
Code Capacity: 8*(5MP-Lite@12/1080P-Lite@25)fps
8CH Playback
Support SMD (Human/Vehicle Clasification For 8CH)
Support 1CH Face Detection
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analoge,AHD,CVI,TVI,IP)
HDMI & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif 2.4, IOS-Andriod FARA VIEW App - Adaptive Iran & International Servers

OHD-8108ZFN-4KL/A4



62.250.000

8CH H.265 **4K-Lite & Real 5MP** XVR
8CH Camera (Analog & IP)
Preview Capacity: 8*(4K-Lite@15/5MP@12)fps
Code Capacity: 8*(4K-Lite@9/5MP@8/4MP@10/1080P@20)fps
8CH Playback
Support SMD (Human/Vehicle Classification For 8CH)
Support 1CH Face Detection (With Special Firmware Upgrade / Not At The Same Time As SMD)
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analog, AHD, CVI, TVI, IP)
HDMI 4K & VGA Video Simultaneous Output - Analog Video Output (BNC)
1 SATA HDD Up to 10TB (Change Adaptor to 12V/5A)
4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif 2.4, IOS-Android FARA VIEW App, Adaptive Iran & International Servers

OHD-8108ZHN-4KL/A4



NEW AI Chipset



62.250.000

8CH H.265 **4K-Lite & Real 5MP** XVR
8CH Camera + 4CH IP Camera
Preview Capacity: 8*(4K-Lite@15/5MP@12)fps
Code Capacity: 8*(4K-Lite@9/5MP@8/1080P@20)fps
8CH Playback
Support SMD (Human/Vehicle Classification For 8CH)
Support Face Detection
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analog, AHD, CVI, TVI, IP)
HDMI 4K & VGA Video Simultaneous Output - Analog Video Output (BNC)
1 SATA HDD Up to 10TB
4/1CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif 2.4, IOS-Android FARA VIEW App, Adaptive Iran & International Servers

OHD-6108ZHN-A4



NEW AI Chipset



44.200.000

8CH H.265 5MP-Lite XVR
8CH Camera + 4CH IP Camera
Preview Capacity: 8*(5MP-Lite@20)fps
Code Capacity: 8*(5MP-Lite@12/1080P@15)fps
8CH Playback (4CH@12fps + 4CH@1fps)
Support SMD (Human/Vehicle Classification For 8CH)
Support 1CH Face Detection
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analog, AHD, CVI, TVI, IP)
HDMI & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
4/1 CH Audio In/Out, 2*USB - 1*10/100 Mbps LAN Interface
P2P support, Onvif, IOS-Android FARA VIEW App - Adaptive Iran & International Servers

OHD-6116ZFN-A1



66.800.000

16CH H.265 **5MP-Lite** XVR
16CH Camera + 4CH IP Camera
Preview Capacity: 16*(5MP-Lite@12)fps
Code Capacity: 16*(5MP-Lite@6/4MP-Lite@8/1080P-Lite@16)fps
16CH Playback
Support SMD (Human/Vehicle Classification For 16CH)
Support 1CH Face Detection (With Special Firmware Upgrade / Not At The Same Time As SMD)
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analog, AHD, CVI, TVI, IP)
HDMI & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif 2.4, IOS-Android FARA VIEW App - Adaptive Iran & International Servers

OHD-8116ZHN-4KL/A4



NEW AI Chipset



94.300.000

16CH H.265 **4K-Lite & Real 5MP** XVR
16CH Camera + 4CH IP Camera
Preview Capacity: 16*(4K-Lite@15/5MP@12)fps
Code Capacity: 16*(4K-Lite@9/5MP@8/1080P@20)fps
16CH Playback
Support SMD (Human/Vehicle Classification For 16CH)
Support 1CH Face Detection
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analog, AHD, CVI, TVI, IP)
HDMI 4K & VGA Video Simultaneous Output - Analog Video Output (BNC)
1 SATA HDD Up to 10TB
4/1CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif 2.4, IOS-Android FARA VIEW App - Adaptive Iran & International Servers

OHD-8232ZHN-4KL/A4



NEW AI Chipset



206.850.000

32CH H.265 **4K-Lite & Real 5MP** XVR
32CH Camera (Analog & IP)
Preview Capacity: 32*(4K-Lite@15/5MP@12)fps
Code Capacity: 32*(4K-Lite@7/5MP@6/1080P@15)fps
16CH Playback
Support SMD (Human/Vehicle Classification For 16CH)
Support Face Detection
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analog, AHD, CVI, TVI, IP)
HDMI 4K & VGA Video Simultaneous Output - Analog Video Output (BNC)
2 SATA HDD Each Up to 10TB
4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif 2.4, IOS-Android FARA VIEW App - Adaptive Iran & International Servers