



لیست قیمت محصولات TVI/CVI ایتینا فروردین ماه ۱۴۰۵






PHOBOS 500WSF-SA

5.0 Megapixel HDTVI Camera
 1/2.8" Starlight CMOS Sensor
 2.8mm F1.2 Starlight Fixed Lens
 2560(H) × 1920(V) Resolution
 DWDR, 3DNR, AWB, BLC
 4 Power LED
 40m Warmlight Length
 OSD Menu by UTC (output 4-in-1)
 Built in MIC

28.700.000





PHOBOS 200WSF-SCA

2.0 Megapixel HDTVI Camera
 1/2.9" Starlight CMOS Sensor
 2.8mm F1.2 Starlight Fixed Lens
 1920(H) × 1080(V) Resolution
 DWDR, 3DNR, AWB, BLC
 4 Power LED
 40m Warmlight Length
 OSD Menu by UTC (output 4-in-1)
 Built in MIC
 Support Audio in TVI & CVI Mode
 (Compatible With Dahua Recorder)

22.100.000





DEVRA 200DSF-SCA

2.0 Megapixel HDTVI Camera
 1/2.9" Starlight CMOS Sensor
 2.8mm F1.2 Starlight Fixed Lens
 1920(H) × 1080(V) Resolution
 DWDR, 3DNR, AWB, BLC
 2 Dual LED
 30m Warmlight, 40m IR Length
 OSD Menu by UTC (output 4-in-1)
 Built in MIC
 Support Audio in TVI & CVI Mode
 (Compatible With Dahua Recorder)

23.500.000





TITAN 200DSF-SCA

2.0 Megapixel HDTVI Camera
 1/2.9" Starlight CMOS Sensor
 2.8mm F1.2 Starlight Fixed Lens
 1920(H) × 1080(V) Resolution
 DWDR, 3DNR, AWB, BLC
 3 Dual EXIR LED
 30m Warmlight, 40m IR Length
 OSD Menu by UTC (output 4-in-1)
 Built in MIC
 Support Audio in TVI & CVI Mode
 (Compatible With Dahua Recorder)
 IP67, Metal Ball, Easy Installation

30.400.000





TITAN 200WSF-SCA

2.0 Megapixel HDTVI Camera
 1/2.9" Starlight CMOS Sensor
 2.8mm F1.2 Starlight Fixed Lens
 1920(H) × 1080(V) Resolution
 DWDR, 3DNR, AWB, BLC
 3 EXIR LED
 30m Warmlight Length
 OSD Menu by UTC (output 4-in-1)
 Built in MIC
 Support Audio in TVI & CVI Mode
 (Compatible With Dahua Recorder)
 IP67, Metal Ball, Easy Installation

29.300.000





TITAN 500DSF-SA

5.0 Megapixel HDTVI Camera
 1/2.8" Starlight CMOS Sensor
 2.8mm F1.2 Starlight Fixed Lens
 2560(H) × 1920(V) Resolution
 DWDR, 3DNR, AWB, BLC
 3 Dual EXIR LED
 30m Warmlight, 40m IR Length
 OSD Menu by UTC (output 4-in-1)
 Built in MIC
 IP67, Metal Ball, Easy Installation

37.700.000



TITAN 500WSF-SA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP67, Metal Ball, Easy Installation

36.400.000



TETIS 200WSF-SCA

2.0 Megapixel HDTVI Camera
1/2.9" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
Support Audio in TVI & CVI Mode
(Compatible With Dahua Recorder)
IP67, Metal Ball, Easy Installation

29.100.000



TETIS 500WSF-SA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP67, Metal Ball, Easy Installation

36.400.000



ARTEMIS 200ASF-SL

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
24 SMD LED
45m IR Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case

22.600.000



HELIX 200DLF-S

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 Dual EXIR LED
30m Warmlight, 40m IR Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case, Easy Installation

27.700.000



HELIX 200WLF-S

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case, Easy Installation

26.700.000



HELIX 200WLF-S/28

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case, Easy Installation

26.700.000



HELIX 500DLF-SA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 Dual EXIR LED
30m Warmlight, 40m IR Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

36.600.000



HELIX 500WLF-SA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

35.600.000



AWASIS 200DLF-S

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 Dual EXIR LED
30m Warmlight, 40m IR Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case, Easy Installation

28.600.000



AWASIS 200WLF-S

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case, Easy Installation

27.600.000



AWASIS 500DLF-SA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 Dual EXIR LED
30m Warmlight, 40m IR Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

37.500.000



AWASIS 500WLF-SA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

36.500.000



NESTOR 200DLF-S

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Dual EXIR LED
40m Warmlight, 60m IR Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case

29.900.000



NESTOR 200WLF-S

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
4 EXIR LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case

28.900.000



NESTOR 500DLF-SA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Dual EXIR LED
40m Warmlight, 60m IR Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case

38.900.000



NESTOR 500WLF-SA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 EXIR LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case

37.900.000



POLARIS 200WLF-S

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
4 EXIR LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case, Easy Installation

29.500.000



POLARIS 500DLF-SA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Dual EXIR LED
40m Warmlight, 60m IR Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

39.400.000



POLARIS 500WLF-SA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 EXIR LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

38.500.000



AVILON 500WLF-SA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Power EXIR LED
50m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

40.600.000



CAPELLA 200WLF-SL

2.0 Megapixel Camera
1/2.9" CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Sunny LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case, Easy Installation

25.000.000



CAPELLA 500WLF-SA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Sunny LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

34.400.000



CARPO 200WLF-SL

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
8 Power LED
50m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Plastic (Makrolon) Case
Easy Installation

21.750.000



AVIX 200WLF-S

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case, Easy Installation

26.400.000



ERIS 200WLF-S

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
2 Power LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case

26.300.000

SMD **OHD-6104ZFN-A1****90.800.000**

4CH H.265 **5MP-Lite** XVR
4CH Camera + 1CH IP Camera
Preview : 4*(5MP-Lite@20)fps
Record : 4*(5MP-Lite@12/4MP-Lite@17/1080P@15/1080P-Lite@25)fps
4CH Playback
Support 4CH SMD, 4CH Perimeter/Tripwire
Support Face Detection 1CH (Special Firmware, Not At The Same Time As SMD)
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analoge,AHD,CVI,TVI,IP)
HDMI 1080P & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

SMD **OHD-8104ZFN-4KL/A4****122.700.000**

4CH H.265 **Real 5MP** XVR
4CH Camera (Analog & IP)
Preview : 4*(5MP@12)fps
Record : 4*(5MP@12/4MP@15/1080P@25)fps
4CH Playback
Support SMD (Human/Vehicle Clasification For 4CH)
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analoge,AHD,CVI,TVI,IP)
HDMI 4K & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

SMD **HISILICON**
NEW AI Chipset**OHD-8104ZHN-4KL/A4****125.600.000**

4CH H.265 **4K-Lite & Real 5MP** XVR
4CH Camera + 2CH IP Camera
Preview : 4*(8MP-Lite@15/5MP@12)fps
Record : 4*(8MP-Lite@15/5MP@12/4MP@16/1080P@25)fps
4CH Playback (2CH@15fps + 2CH@1fps)
Support 4CH SMD, 4CH Perimeter/Tripwire
Support Face Detection
Support LPD
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analoge,AHD,CVI,TVI,IP)
HDMI 4K & VGA Video Simultaneous Output, Analog Video Output (BNC)
1 SATA HDD Up to 10TB
4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface, RS-485 Port
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

SMD **New Ultra Model****OHD-6108ZFU-A1****115.000.000**

8CH H.265 **5MP-Lite** XVR
8CH Camera + 2CH IP Camera
Preview : 8*(5MP-Lite@12)fps
Record : 8*(5MP-Lite@12/1080P-Lite@25)fps
8CH Playback
Support 8CH SMD, 8CH Perimeter/Tripwire
Support Face Detection
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analoge,AHD,CVI,TVI,IP)
HDMI & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

SMD **HISILICON**
NEW AI Chipset**OHD-6108ZHN-A4****122.500.000**

8CH H.265 **5MP-Lite** XVR
8CH Camera + 4CH IP Camera
Preview : 8*(5MP-Lite@20)fps
Record : 8*(5MP-Lite@12/1080P@15)fps
8CH Playback (4CH@12fps + 4CH@1fps)
Support 8CH SMD, 4CH Perimeter/Tripwire
Support Face Detection
Support LPD
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analoge,AHD,CVI,TVI,IP)
HDMI & VGA Video Simultaneous Output, Analog Video Output (BNC)
1 SATA HDD Up to 10TB
4/1 CH Audio In/Out, 2*USB - 1*10/100 Mbps LAN Interface, RS-485 Port
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

SMD **OHD-8108ZFN-4KL/A4****181.000.000**

8CH H.265 **4K-Lite & Real 5MP** XVR
8CH Camera (Analog & IP)
Preview : 8*(4K-Lite@15/5MP@12)fps
Record : 8*(4K-Lite@9/5MP@8/4MP@10/1080P@20)fps
8CH Playback
Support SMD (Human/Vehicle Clasification For 8CH)
Support Face Detection (Special Firmware, Not At The Same Time As SMD)
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analoge,AHD,CVI,TVI,IP)
HDMI 4K & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB (Change Adaptur to 12V/5A)
4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers



HISILICON
NEW AI Chipset



OHD-8108ZHN-4KL/A4

184.700.000

8CH H.265 **4K-Lite & Real 5MP** XVR
8CH Camera + 4CH IP Camera
Preview : 8*(4K-Lite@15/5MP@12)fps
Record : 8*(4K-Lite@9/5MP@8/1080P@20)fps
8CH Playback
Support 8CH SMD, 4CH Perimeter/Tripwire
Support Face Detection
Support LPD
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analoge,AHD,CVI,TVI,IP)
HDMI 4K & VGA Video Simultaneous Output, Analog Video Output (BNC)
1 SATA HDD Up to 10TB
4/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface, RS-485 Port
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers



OHD-6116ZFN-A1

207.500.000

16CH H.265 **5MP-Lite** XVR
16CH Camera + 4CH IP Camera
Preview : 16*(5MP-Lite@12)fps
Record : 16*(5MP-Lite@6/4MP-Lite@8/1080P-Lite@16)fps
16CH Playback
Support SMD (Human/Vehicle Clasification For 16CH)
Support Face Detection (Special Firmware, Not At The Same Time As SMD)
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analoge,AHD,CVI,TVI,IP)
HDMI & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers



HISILICON
NEW AI Chipset



OHD-6116ZHN-A1

214.000.000

16CH H.265 **5MP-Lite** XVR
16CH Camera + 4CH IP Camera
Preview : 16*(5MP-Lite@12)fps
Record : 16*(5MP-Lite@6/4MP-Lite@8/1080P-Lite@16)fps
16CH Playback
Support 16CH SMD, 8CH Perimeter/Tripwire
Support Face Detection
Support LPD
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analoge,AHD,CVI,TVI,IP)
HDMI & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers



HISILICON
NEW AI Chipset



OHD-8116ZHN-4KL/A4

279.500.000

16CH H.265 **4K-Lite & Real 5MP** XVR
16CH Camera + 4CH IP Camera
Preview : 16*(4K-Lite@15/5MP@12)fps
Record : 16*(4K-Lite@9/5MP@8/1080P@20)fps
16CH Playback
Support 16CH SMD, 8CH Perimeter/Tripwire
Support Face Detection
Support LPD
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analog,AHD,CVI,TVI,IP)
HDMI 4K & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
4/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface, RS-485 Port
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers



HISILICON
NEW AI Chipset



OHD-8232ZHN-4KL/A4

593.500.000

32CH H.265 **4K-Lite & Real 5MP** XVR
32CH Camera (Analog & IP)
Preview : 32*(4K-Lite@15/5MP@12)fps
Record : 32*(4K-Lite@7/5MP@6/1080P@15)fps
16CH Playback
Support 16CH SMD, 8CH Perimeter/Tripwire
Support Face Detection
Support LPD
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analog,AHD,CVI,TVI,IP)
HDMI 4K & VGA Video Simultaneous Output, Analog Video Output (BNC)
2 SATA HDD Each Up to 10TB
4/1 CH Audio In/Out, 4/1 Alarm In/Out, 2*USB
1*10/100/1000 Mbps LAN Interface, RS-485 Port
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers



لیست قیمت محصولات IP اپتینا فروردین ماه ۱۴۰۵



TETIS 2000PUWSF-SAF-IF

1/2.9" 2.4Megapixel **New** Starlight CMOS Sensor
Main Stream 2.0MP (1920*1080)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

47.500.000



TETIS 2000PWSF-SAF-IF

1/2.9" 2.4Megapixel Starlight CMOS Sensor
Main Stream 2.0MP (1920*1080)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

47.500.000



TITAN 2000PWSF-SAF-IF

1/2.9" 2.4Megapixel Starlight CMOS Sensor
Main Stream 2.0MP (1920*1080)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

47.500.000



TITAN 5000PIWSF-SAF-IF

1/3" 5.0Megapixel Starlight CMOS Sensor
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Integrated PoE (Onboard)
Fara View Mobile Monitoring, VMS Monitoring

59.300.000



TETIS 5000PIWSF-SAF-IF

1/3" 5.0Megapixel Starlight CMOS Sensor
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Integrated PoE (Onboard)
Fara View Mobile Monitoring, VMS Monitoring

59.300.000



TITAN 5000PWSF-SAH-IF

1/3" 5.0Megapixel Starlight CMOS Sensor, **HiSilicon Chipset**
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

62.900.000



TETIS 5000PWSF-SAF-IF

1/3" 5.0Megapixel Starlight CMOS Sensor
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

62.900.000



TITAN 5000PWSF-SAF-IF

1/3" 5.0Megapixel Starlight CMOS Sensor
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

62.900.000



TETIS 5100PWSF-SAF-IF

1/2.7" 5.0Megapixel Starlight CMOS Sensor
Pro Series 16:9 Ratio
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
120db WDR, 3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

83.000.000



TITAN 5100PWSF-SAF-IF

1/2.7" 5.0Megapixel Starlight CMOS Sensor
Pro Series 16:9 Ratio
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
120db WDR, 3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

83.000.000



HELIX 2000PUWLF-SAF-IF

1/2.9" 2.4Megapixel **New** Starlight CMOS Sensor
Main Stream 2.0MP (1920*1080)@25/30fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

46.300.000



HELIX 2000PWLF-SAF-IF

1/2.9" 2.4Megapixel Starlight CMOS Sensor
Main Stream 2.0MP (1920*1080)@25/30fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

46.300.000



AWASIS 5000PWLF-SAH-IF

1/3" 5.0Megapixel Starlight CMOS Sensor, **HiSilicon Chipset**
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

60.800.000



AWASIS 5000PWLF-SAF-IF

1/3" 5.0Megapixel Starlight CMOS Sensor
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

60.800.000



POLARIS 5000PWL-IF

1/3" 5.0Megapixel Starlight CMOS Sensor, **HiSilicon Chipset**
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
4 EXIR LED, 40m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

63.000.000



POLARIS 5000PWL-SAF-IF

1/3" 5.0Megapixel Starlight CMOS Sensor
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
4 EXIR LED, 40m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

63.000.000



CARINA 5000PWL-IF

1/3" 5.0Megapixel Starlight CMOS Sensor, **HiSilicon Chipset**
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
5 Power EXIR LED, 60m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

70.600.000



AVILON 5100PWL-SAF-IF

1/2.7" 5.0Megapixel Starlight CMOS Sensor
Pro Series 16:9 Ratio, Dual Board (Processor & Sensor)
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
120db WDR, 3DNR, HLC, BLC
4 Power EXIR LED, 50m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

84.200.000



CARINA 5000PWLF-ZAF-IF

1/1.8" 5.0Megapixel Super LowLight CMOS Sensor
Dual Board (Processor & Sensor)
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
4.0mm F1.0 Starlight Advanced Fixed Lens
Built in Microphone
Digital WDR, 3DNR, HLC, BLC
5 Power EXIR LED, 60m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection)
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

114.500.000



NESTOR 8100PWLF-SAF-IF

1/2.8" 8.0Megapixel SONY STARVIS IMX415 Sensor
Dual Board (Processor & Sensor)
Main Stream 8.0MP (3840*2160)@20fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
120db WDR, 3DNR, HLC, BLC
4 EXIR LED, 40m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
Licence Plate Detection (LPD With Software Update)
IP67 Metal Case, 12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

118.500.000



AVILON 8100PWLF-SAF-IF

1/2.8" 8.0Megapixel SONY STARVIS IMX415 Sensor
Dual Board (Processor & Sensor)
Main Stream 8.0MP (3840*2160)@20fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
120db WDR, 3DNR, HLC, BLC
4 Power EXIR LED, 50m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
Licence Plate Detection (LPD With Software Update)
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

127.500.000



KAVARIA 8100PWLF-SAF-IF

1/2.8" 8.0Megapixel SONY STARVIS IMX415 Sensor
Dual Board (Processor & Sensor)
Main Stream 8.0MP (3840*2160)@20fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
120db WDR, 3DNR, HLC, BLC
4 Power EXIR LED, 50m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
Licence Plate Detection (LPD With Software Update)
IP67 Metal Case, 12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

127.500.000



AVILON 8100PDLF-SAF-ZIF

1/2.8" 8.0Megapixel SONY STARVIS IMX415 Sensor
Dual Board (Processor & Sensor)
Main Stream 8.0MP (3840*2160)@20fps
H.265/H.264 Encoding, Dual Stream
2.8~12mm F1.6 Starlight Advanced **Motorized** Lens
Built in Microphone
120db WDR, 3DNR, HLC, BLC
(6+4) Dual EXIR LED, 80m Warmlight, 90m IR Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
Licence Plate Detection (LPD With Software Update)
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

193.500.000



AVILON 8100PDLF-SAF-IF16

1/2.8" 8.0Megapixel SONY STARVIS IMX415 Sensor
Dual Board (Processor & Sensor)
Main Stream 8.0MP (3840*2160)@20fps
H.265/H.264 Encoding, Dual Stream
16mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
120db WDR, 3DNR, HLC, BLC
(6+4) Dual EXIR LED, 80m Warmlight, 90m IR Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
Licence Plate Detection (LPD With Software Update)
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

144.000.000

SMD



ONR-7110F-4K

CALL

10CH H.265 4K (8.0MP) NVR
80Mbps Incoming Bandwidth
10Ch Live View, Up to 8.0MP Resolution for Preview & Playback
Decode Capacity : 1*(4K@25fps)
Playback 10CH (Main Stream + Sub Stream)
Ai By Camera (Full Channel SMD, Face Detection, Perimeter, Tripwire)
Digital Audio Support
HDMI 4K & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1 CH Audio Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

SMD



HISILICON
NEW AI Chipset



ONR-8110i-4K

116.500.000

10CH H.265 4K (8.0MP) NVR
100Mbps Incoming Bandwidth
10Ch Live View, Up to 8.0MP Resolution for Preview & Playback
Decode Capacity : 1*(4K@25fps)
Playback 10CH (Main Stream + Sub Stream)
Ai By Camera (Full Channel LPD, SMD, Perimeter, Tripwire)
Ai By NVR (1Ch Face Recognition, 4Ch SMD, 4Ch Perimeter/Tripwire)
Digital Audio Support
HDMI 4K & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1 CH Audio Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

SMD



HISILICON
NEW AI Chipset



ONR-8120H-4K

164.000.000

20Ch H.265 4K (8.0MP) NVR
160Mbps Incoming Bandwidth
20Ch Live View, Up to 8.0MP Resolution for Preview & Playback
Decode Capacity : 2*(4K@25fps)
Playback 16Ch (Main Stream + Sub Stream)
Ai By Camera (Full Channel LPD, SMD, Face Detection, Perimeter, Tripwire)
Ai By NVR (4Ch SMD, 4Ch Face Detection, 4Ch Perimeter/Tripwire)
Digital Audio Support
HDMI 4K & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1 Ch Audio Out, 3*USB 2.0, 1*10/100/1000 Mbps LAN Interface, RS-485
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers



ONR-8120i-4K

156.600.000

20Ch H.265 4K (8.0MP) NVR
120Mbps Incoming Bandwidth
20Ch Live View, Up to 8.0MP Resolution for Preview & Playback
Decode Capacity : 4*(4K@25fps)
Playback 16Ch (Main Stream + Sub Stream)
Ai By Camera (Full Channel LPD, SMD, Perimeter, Tripwire)
Ai By NVR (1Ch Face Recognition, 4Ch SMD, 4Ch Perimeter/Tripwire)
Digital Audio Support
HDMI 4K & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1 Ch Audio Out, 3*USB 2.0, 1*10/100/1000 Mbps LAN Interface, RS-485
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers



HISILICON
NEW AI Chipset



ONR-8132H-4K

198.000.000

32Ch H.265 4K (8.0MP) NVR
200Mbps Incoming Bandwidth
32Ch Live View, Up to 8.0MP Resolution for Preview & Playback
Decode Capacity : 4*(4K@25fps)
Playback 16Ch (Main Stream + Sub Stream)
Ai By Camera (Full Channel LPD, SMD, Face Detection, Perimeter, Tripwire)
Ai By NVR (8Ch SMD, 4Ch Face Detection, 8Ch Perimeter/Tripwire)
Digital Audio Support
HDMI 4K & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1 Ch Audio Out, 3*USB 2.0, 1*10/100/1000 Mbps LAN Interface, RS-485
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

FARA - Z MODEM



FZ4000G

43.700.000

4G/LTE USB Modem
ASR1803S chip platform
Built-in antenna / Plug and Play
FDD-LTE 150Mbps & TDD-LTE 130Mbps Cat4
Compatible With Z Series XVR & NVR
Power : 5~18V/0.5~1A
89.6mm*28.6mm*13mm / 50g

این مودم با دستگاه های سری زد همخوانی کامل داشته و از طریق اتصال یو اس بی، اینترنت پر سرعت را در اختیار کاربر می گذارد. به وسیله این مودم می توان از قابلیت ارسال اس ام اس دستگاه های سری زد استفاده نمود



FARA AI ALARM BOX

33.200.000

3 Output Relay Box
1 Output With 12VDC
1 RJ45 Web Management Interface
Compatible With Z Series XVR
12VDC Input (Without Adaptor)

این محصول به وسیله کابل شبکه به رکوردرهای سری زد متصل شده و با تعریف و پیاده سازی سناریوهای مختلف از طریق رکوردر و منوی خود محصول می توان از قابلیت های تشخیص انسان و خودروی دوربین و رکوردر در جهت فعال سازی خروجی محصول استفاده نمود تا خروجی تجهیزاتی از قبیل آژیر، تلفن کننده فرمان به دزدگیر و سایر تجهیزات فرمان پذیر را فعال کرد و از دوربین ها به عنوان دتکتور محیطی با هوش مصنوعی و دقت بسیار بالا استفاده نمود